






Mobile 2-Post Lift FHB 3000 for cars

	Description	Article-No.	Price
	<p>Mobile 2-post lift FHB3000-SS (for cars)</p> <p>Capacity: 3 t Load support: 4 swivel arms, symmetric, 600 - 1070 mm Lift pad height: Minimum 110 mm Lifting height: 1850 mm Drive-in width: 2000 mm Lifting time: Approx. 40 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 16A Load securing: Hydraulic and mechanical locks Travelling device: Detachable wheel handle, 2 wheels Protection class: IP 54 Colour: Orange RAL2004</p>	FHB3000-01	7.470 €
	<p>Mobile 2-post Lift FHB3000-SL (for cars and vans)</p> <p>Capacity: 3 t Load support: 4 swivel arms, asymmetric, front 600 - 1070 mm, rear 700 - 1550 mm Lift pad height: Minimum 110 mm Lifting height: 1850 mm Drive-in width: 2000 mm Lifting time: Approx. 40 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 16A Load securing: Hydraulic and mechanical locks Travelling device: Detachable wheel handle, 2 wheels Protection class: IP 54 Colour: Orange RAL2004</p>	FHB3000-02	7.990 €
	<p>Bio-Oil for lift FHB3000 (Accessory, instead standard oil) Synthetic oil, biodegradable, -10° to +70° C</p>	FHB3000-SYN	100 €
	<p>Distance Tubes LA02 for lift FHB3000 (accessory for lift FHB3000)</p> <p>Use: For vans and S.U.V., extension of support height by 100 mm Delivery: 4 pieces</p>	FHB3000-LA02	168 €

Mobile 2-Post Lift FHB 3000 for cars

	Description	Article-No.	Price
	<p>Packing for lift FHB3000 (standard packing)</p> <p>Version: For truck transport, packing open Dimensions: 315 x 235 x 90 cm (l x w x h) Weight: 940 kg Delivery: Lift completely assembled Attention: Unloading at site not included, suitable fork lift to be available, length of forks minimal 1.6 m</p>	FHB3000-PACK1	0 €
	<p>Export Packing for Lift FHB3000 (net price)</p> <p>Version: 1 wooden crate, heat-treated wood Dimensions: 225 x 120 x 100 cm (l x w x h) Weight: 1000 kg Delivery: Lift disassembled Attention: Unloading at site not included</p>	FHB3000-Verschlag	335 €
	<p>Ascending Device FA3 (accessory for lift FHB3000)</p> <p>Capacity: 2.75 t Runway length: 3500 mm Runway width: 430 mm Runway height: 110 mm Use: Mounting on swivel arms of lift FHB3000 Delivery: 2 runways, 2 cross beams</p>	FHB3000-FA3	1.990 €
	<p>Axle Lift MH20 (accessory for FA3)</p> <p>Capacity: 2 t Lifting stroke: 270 mm Drive: Pneumatic, 5 bar Chassis: Movable between runways</p>	FHB3000-MH20	2.190 €
	<p>Mobile 2-post lift FHB3000-SS-TORO (for mowing machines and golf carts)</p> <p>Capacity: 3 t without device FA-TORO 2.5 t with device FA-TORO Load support: 4 swivel arms, symmetric, 600 - 1070 mm Lift pad height: Minimum 110 mm Lifting height: 1850 mm Drive-in width: 2300 mm (extended width) Lifting time: Approx. 40 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 16A Load securing: Hydraulic and mechanical locks Travelling device: Detachable wheel handle, 2 wheels Protection class: IP 54 Colour: Orange RAL2004</p> <p>Attention: Required accessory: Ascending Device FA-TORO</p>	FHB3000-03	7.850 €

Mobile 2-Post Lift FHB 3000 for cars

	Description	Article-No.	Price
	<p>Ascending Device FA-TORO (accessory for lift FHB3000-SS/S-TORO)</p> <p>Capacity: 2.75 t</p> <p>Load support: 4 wheel platforms, 370 x 350 mm, adjustable for varying track widths and wheel bases, even for three wheelers</p> <p>Drive-on height: 100 mm</p> <p>Use: Mounting onto swivel arms of lift FHB3000-TORO with drive-in-width 2300 mm</p> <p>Delivery: 4 wheel platforms, 2 cross beams</p>	FHB3000-03FATORO	1.890 €