





Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Mobile Column Lift EHB807V11-4 Premium (for heavy duty vehicles)</p> <p>Capacity: 4 x 7.5 t = 30 t Columns: 1 master, 3 slaves Wheel fork: Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles</p> <p>Lifting stroke: 1725 mm Speed: Up 1.5 m/min., Down 1.7 m/min. (approx.) Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A Control: Smooth synchronisation by proportional valves Load securing: Hydraulic and mechanical locks Operation: At Master: Single/ Pair / All, menu control with display At each column: Up / Down / Slow</p> <p>Cable connection: 1 power supply cable 10 m, 3 interconnect cables 10 m with plugs on both ends, open circuit</p> <p>Travelling device: At each column, rear wheel jack and front wheels spring-loaded</p> <p>Protection class: IP 65 Colour: Orange RAL2004</p>	<p>EHB807V11U04</p>	<p>24.550 €</p>
	<p>Mobile Column Lift EHB807V11-6 Premium (for heavy duty vehicles)</p> <p>Capacity: 6 x 7.5 t = 45 t Columns: 1 master, 5 slaves Wheel fork: Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles</p> <p>Lifting stroke: 1725 mm Speed: Up 1.5 m/min., Down 1.7 m/min. (approx.) Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A Control: Smooth synchronisation by proportional valves Load securing: Hydraulic and mechanical locks Operation: At Master: Single/ Pair/ All, menu control and display At each column: Up / Down / Slow</p> <p>Cable connection: 1 power supply cable 10 m, 5 interconnect cables 10 m with plugs on both ends, open circuit</p> <p>Travelling device: At each column, rear wheel jack and front wheels spring-loaded</p> <p>Protection class: IP 65 Colour: Orange RAL2004</p>	<p>EHB807V11U06</p>	<p>36.550 €</p>




Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	Master Column EHB807V11-H Premium (for heavy duty vehicles)	EHB807V11U0H	6.550 €
	Capacity:	7.5 t	
	Wheel fork:	Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles	
	Lifting stroke:	1725 mm	
	Speed:	Up 1.5 m/min., Down 1,7 m/min. (approx.)	
	Drive:	Electro-hydraulic	
	Connection:	400V / 3Ph / 50Hz / 35A	
	Control:	Smooth synchronisation by proportional valves	
	Load securing:	Hydraulic and mechanical locks	
	Operation:	Up / down / slow Modes: single / pair / all Menu control with display	
	Cable connection: Power supply cable 10 m		
	Travelling device: Rear wheel jack and front wheels spring-loaded		
	Protection class: IP 65		
	Colour: Orange RAL2004		
	One master suitable for up to 5 slaves (set of 6). System extendable up to 24 columns (4 masters + 20 slaves). Several masters can work within one lift set, then extra interconnect cables are required.		
	Slave Column EHB807V11-N Premium (for heavy duty vehicles)	EHB807V11U0N	6.000 €
	Capacity:	7.5 t	
	Wheel fork:	Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles	
	Lifting stroke:	1725 mm	
	Speed:	Up 1.5 m/min., Down 1,7 m/min. (approx.)	
	Drive:	Electro-hydraulic	
	Connection:	400V / 3Ph / 50Hz	
	Control:	Smooth synchronisation by proportional valves	
	Load securing:	Hydraulic and mechanical locks	
	Operation:	Up / down / slow (without menu control and display)	
	Cable connection: Interconnect cable 10 m, plugs on both ends		
	Travelling device: Rear wheel jack and front wheels spring-loaded		
	Protection class: IP 65		
	Colour: Orange RAL2004		
	All slaves are identical without encodes. To operate one or several slaves a master column is required.		







Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Mobile Column Lift EHB808V11-4 Premium (for heavy duty vehicles)</p> <p>Capacity: 4 x 8.2 t = 32.8 t Columns: 1 master, 3 slaves Wheel fork: Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles</p> <p>Lifting stroke: 1725 mm Speed: Up 1.5 m/min., Down 1.7 m/min. (approx.) Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A Control: Smooth synchronisation by proportional valves Load securing: Hydraulic and mechanical locks Operation: At Master: Single/ Pair/ All, menu control with display At each column: Up / Down / Slow</p> <p>Cable connection: 1 power supply cable 10 m, 3 interconnect cables 10 m with plugs on both ends, open circuit</p> <p>Travelling device: At each column, rear wheel jack and front wheels spring-loaded</p> <p>Protection class: IP 65 Colour: Orange RAL2004</p>	<p>EHB808V11U04</p>	<p>25.550 €</p>
	<p>Mobile Column Lift EHB808V11-6 Premium (for heavy duty vehicles)</p> <p>Capacity: 6 x 8.2 t = 49.2 t Columns: 1 master, 5 slaves Wheel fork: Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles</p> <p>Lifting stroke: 1725 mm Speed: Up 1.5 m/min., Down 1.7 m/min. (approx.) Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A Control: Smooth synchronisation by proportional valves Load securing: Hydraulic and mechanical locks Operation: At Master: Single/ Pair/ All, menu control with display At each column: Up / Down / Slow</p> <p>Cable connection: 1 power supply cable 10 m, 5 interconnect cables 10 m with plugs on both ends, open circuit</p> <p>Travelling device: At each column, rear wheel jack and front wheels spring-loaded</p> <p>Protection class: IP 65 Colour: Orange RAL2004</p>	<p>EHB808V11U06</p>	<p>38.050 €</p>





Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Master Column EHB808V11-H Premium (for heavy duty vehicles)</p> <p>Capacity: 8.2 t Wheel fork: Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles Lifting stroke: 1725 mm Speed: Up 1.5 m/min., Down 1,7 m/min. (approx.) Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A Control: Smooth synchronisation by proportional valves Load securing: Hydraulic and mechanical locks Operation: Up / down / slow Modes: single / pair / all Menu control with display</p> <p>Cable connection: Power supply cable 10 m Travelling device: Rear wheel jack and front wheels spring-loaded Protection class: IP 65 Colour: Orange RAL2004</p> <p>One master suitable for up to 5 slaves (set of 6). To operate more than 6 columns per set, connect further masters; e.g. set of 12 with 2 masters + 10 slaves. System extendable up to 24 columns (4 masters + 20 slaves). Several masters can work within one lift set, then extra interconnect cables are required.</p>	EHB808V11U0H	6.800 €
	<p>Slave Column EHB808V11-N Premium (for heavy duty vehicles)</p> <p>Capacity: 8.2 t Wheel fork: Adjustable up to 22.5" / Ø 1140 mm, length 385 mm, also for super singles Lifting stroke: 1725 mm Speed: Up 1.5 m/min., Down 1,7 m/min. (approx.) Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz Control: Smooth synchronisation by proportional valves Load securing: Hydraulic and mechanical locks Operation: Up / down / slow (without menu control and display)</p> <p>Cable connection: Interconnect cable 10 m, plugs on both ends Travelling device: Rear wheel jack and front wheels spring-loaded Protection class: IP 65 Colour: Orange RAL2004</p> <p>All slaves are identical without encodes. To operate one or several slaves a master column is required.</p>	EHB808V11U0N	6.250 €
	<p>Remote Control for Lift EHB Premium (accessory)</p> <p>Handset with 10 m cable, at master column, operation Up / Down / E-Stop</p>	EHB807RC	152 €






Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	Bio Oil for Column EHB807/808 Premium (accessory, instead of standard oil) Synthetic oil, biodegradable, -10° to +70°C	EHB807SYN	100 €
	Height Limit for Lift EHB Premium (accessory) Lift will stop at the adjustable top height, per lift set of 4 or set of 6	EHB807HL	183 €
	Intermediate Stop for Lift EHB Premium (accessory) Stop at the adjustable intermediate height, per lift set of 4 or set of 6	EHB807HS	183 €
	Load Checking for Column EHB Premium (accessory) Load Mode: Stops if vehicle is lowered onto an obstruction, display of load in „kg“ Pick-up mode: Common synchron operation after all columns have taken over their loads / reached their load points	EHB807LC	528 €
	Lighting Kit for Column EHB Premium (accessory) 2 fluorescent lamps, IP65, Shock-oil resisting	EHB807LIGHT	487 €
	Master Display for Slave Column EHB Premium (accessory) With menu control and display	EHB807MD	274 €






Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Interconnect Cable for Column EHB Premium (accessory)</p> <p>Version: Length 10 m, pluggable on both ends Use: Required to connect multiple masters</p>	<p>EHB807KAB10</p>	<p>218 €</p>
	<p>Hydraulic Wheel Jack for Column EHB Premium (accessory, instead of standard wheels)</p> <p>Version: For rear and front wheels Ground clearance: Rear = 90 mm, front = 50 mm Use: To move column on uneven ground</p>	<p>EHB807TDH</p>	<p>611 €</p>
	<p>Extended Wheel Forks for Column EHB Premium (accessory, instead of standard forks)</p> <p>Capacity: 7.5 t Length: 510 mm Delivery: Incl. extension set for column's legs Note: Not available in combination with Hydraulic Wheel Jack</p>	<p>EHB807WF510</p>	<p>317 €</p>
	<p>Truck Crossbeam TRE16 for EHB Premium (accessory)</p> <p>Capacity: 16 t Height: 185 - 450 mm Length: 3000 mm Use: For wheel-free lifting of vehicles at the frame, to be used together with 2 columns EHB Delivery: Incl. 2 rubber pads, 2 extension tubes Colour: Grey RAL7015</p>	<p>EHB807TR16</p>	<p>1.706 €</p>
	<p>Ramps FA25 (accessory for lift EHB707/807)</p> <p>Capacity: 25 t Platform length: 8900 mm Platform width: 700 mm Platform height: 250 mm Use: Platform lift with 4 columns EHB707/808 Delivery: 2 platforms, 2 ascending ramps (fix to floor), 2 cross beams Colour: Grey RAL7015</p>	<p>FA2080000</p>	<p>16.613 €</p>



Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Support Stand LS08 (basic version)</p> <p>Capacity: 8.2 t Height: 535 - 790 mm Design: Triangle tubes - light and solid Height adjustment: Plug pin, every 50 mm Colour: Grey RAL7015 Weight: 20 kg</p>	LS08	248 €
	<p>Support Stand LS08-SV (basic version + spindle)</p> <p>Capacity: 8.2 t Height: 625 - 930 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 50 mm - Spindle (SV) for fine adjustment Colour: Grey RAL7015 Weight: 24 kg</p>	LS08SV	325 €
	<p>Support Stand MS08-LR (basic version)</p> <p>Capacity: 8.2 t Height: 790 - 1270 mm Design: Triangle tubes - light and solid Height adjustment: Plug pin, every 70 mm Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 30 kg</p>	MS08LR	343 €
	<p>Support Stand MS08-LR-SV (basic version + spring)</p> <p>Capacity: 8.2 t Height: 880 - 1410 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 70 mm - Spindle (SV) for fine adjustment Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 34 kg</p>	MS08LRSV	420 €
	<p>Support Stand HS08LR (basic version)</p> <p>Capacity: 8.2 t Height: 1260 - 1990 mm Design: Triangle tubes - light and solid Height adjustment: Plug pin, every 65 mm Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 40 kg</p>	HS08LR	409 €

Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Support Stand HS08-LR-FV (basic version + spring)</p> <p>Capacity: 8.2 t Height: 1260 - 1990 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 65 mm - Spring assistance (FV)</p> <p>Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 43 kg</p>	HS08LRFV	465 €
	<p>Support Stand HS08-LR-FV-SV (basic version + spring + spindle)</p> <p>Capacity: 8.2 t Height: 1350 - 2130 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 65 mm - Spring assistance (FV) - Spindle (SV) for fine adjustment</p> <p>Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 47 kg</p>	HS08LRFVSV	542 €
	<p>Wheel Carriage RW7.06</p> <p>Capacity: 700 kg Lifting stroke: 550 mm Load support: Adjustable fork for wheels Ø 600-1500 mm, length 600 mm, divided rollers for twin wheels</p> <p>Drive: Hydraulic manual pump Travelling device: 2 fixed rollers, 2 guide wheels Colour: Grey RAL7015</p>	RW1200000	1.328 €
	<p>Wheel Carriage RW5.16</p> <p>Capacity: 500 kg Lifting stroke: 1600 mm Load support: Adjustable fork for wheels Ø 500 - 1800 mm, length 650 mm, divided rollers for twin wheels</p> <p>Drive: Manual winch Travelling device: 2 fixed rollers, 2 guide wheels Colour: Grey RAL7015</p>	RW1300000	1.847 €
	<p>Portable Platform Lift FI2</p> <p>Capacity: 2 t Lifting height: 460 - 1460 mm Platform size: 1500 x 800 mm Drive: Electro-hydraulic Connection: 400V / 50Hz / 3Ph / 16A Operation: Hand set, up/down/e-stop, 1 m cable Travelling device: 2 fixed wheels, 2 guide wheels Colour: Turquoise RAL5018</p>	FI-4560120	6.853 €

Mobile Column Lift EHB Premium for heavy duty vehicles

	Description	Article-No.	Price
	<p>Gear Box Lift GTR2B</p> <p>Capacity: 2 t Lifting height: 800 -1900 mm Load support: Pluggable disc Drive: Pneumatic idle run, manually under load Connection: Compressed air, max. 10 bar Travelling device: 4 guide wheels Colour: Grey RAL7015</p>	GTR2B	3.041 €
	<p>Swivel Plate GP1B (accessory for gearbox lift GTR2B)</p> <p>Dimension: 530 x 380 mm Decline: Adjustable +/- 12° Delivery: incl. rubber supports and belts</p>	GP1B	1.272 €