








## Mobile Column Lift EHB Standard for airport ground vehicles (GSE)

	Description	Article-No.	Price
	<p><b>Mobile column lift EHB705PR249-2</b> (for airport ground vehicles - GSE)</p> <p>Capacity: 2 x 5 t = 10 t            Columns: 1 master, 1 slave column            Load support: Universal fork tines, adjustable, to lift at                              - chassis                              - wheels, size up to 16.00R20, Ø 550 - 1420 mm</p> <p>Fork length: 400 mm            Support height: 80 mm            Lifting stroke: 1700 mm            Speed: Approx. 0.8 m/min.            Drive: Electro-hydraulic            Voltage: 400V / 3Ph / 50Hz / 16A            Control: With hydraulic seat valves            Operation: Up / Down, All / Single, for max. 5 slaves            Cable connection: Power supply cable 10 m, interconnect cable 10 m with plug at 1 end</p> <p>Travelling device: Hydraulic wheel jack at rear, fixed front wheels            Column base: Front legs lowered to 80 mm            Protection class: IP 65            Colour: Orange RAL2004</p>	EHB705PR249U02	12.726 €
	<p><b>Mobile column lift EHB706G1-4 Standard</b> (for airport ground vehicles - GSE)</p> <p>Capacity: 4 x 6.5 t = 26 t            Columns: 1 master, 3 slaves            Load support: Universal fork tines, adjustable, to lift at                              - chassis                              - wheels, size up to 16.00R20, Ø 550 - 1420 mm</p> <p>Fork length: 600 mm            Support height: 100 mm            Lifting stroke: 1700 mm            Speed: Approx. 0.8 m/min.            Drive: Electro-hydraulic            Voltage: 400V / 3Ph / 50Hz / 16A            Control: With hydraulic seat valves            Load securing: Hydraulic and mechanical locks            Operation: From each column, Up / Down, All / Single            Cable connection: 1 power supply cable 10 m, interconnect cable 10 m per column, plug at 1 end, closed circuit</p> <p>Travelling device: Hydraulic wheel jack at rear, fixed front wheels            Column base: Front legs lowered to 88 mm            Protection class: IP 65            Colour: Orange RAL2004</p>	EHB706G10004	27.230 €

## Mobile Column Lift EHB Standard for airport ground vehicles (GSE)

	Description	Article-No.	Price
	<p><b>Mobile Column Lifts EHB710V16-4-PR248 Standard</b> (for airport ground vehicles - GSE)</p> <p>Capacity: 4 x 10 t = 40 t            Columns: 1 master, 3 slaves            Load support: Universal fork tines, adjustable, to lift at                              - chassis                              - wheels, size up to 18.00R25, Ø 550 - 1600 mm</p> <p>Fork length: 450 mm            Support height: 80 mm            Lifting stroke: 1700 mm            Speed: Approx. 0.6 m/min.            Drive: Electro-hydraulic            Voltage: 400V / 3Ph / 50Hz / 32A            Control: With hydraulic seat valves            Load securing: Hydraulic and mechanical locks            Operation: From each column, Up / Down, All / Single            Cable connection: 1 power supply cable 10 m, interconnect cable 10 m                                      per column, plug at 1 end, closed circuit</p> <p>Travelling device: Hydraulic wheel jack for front and rear wheels,                                      at each column</p> <p>Column base: Front legs lowered to 80 mm            Protection class: IP 65            Colour: Orange RAL2004</p>	<p>EHB710V16U04-PR248</p>	<p>37.590 €</p>
	<p><b>Mobile Column Lift EHB715G1-4 Standard</b> (for airport ground vehicles - GSE)</p> <p>Capacity: 4 x 15 t = 60 t            Columns: 1 master, 3 slaves            Load support: Universal fork tines, adjustable, to lift at                              - chassis                              - wheels, size up to 16.00R25, Ø 550 - 1480 mm</p> <p>Fork length: 590 mm            Support height: 90 mm / 70 mm at front            Lifting stroke: 1700 mm            Speed: Approx. 0.6 m/min.            Drive: Electro-hydraulic            Voltage: 400V / 3Ph / 50Hz / 32A            Control: With hydraulic seat valves            Load securing: Hydraulic and mechanical locks            Operation: From each column, Up / Down, All / Single            Cable connection: 1 power supply cable 10 m, interconnect cable 15 m                                      per column, plug at 1 end, closed circuit</p> <p>Travelling device: Hydraulic wheel jack for front and rear wheels,                                      at each column</p> <p>Column base: Front legs lowered to 60 / 95 mm            Protection class: IP 65            Colour: Orange RAL2004</p>	<p>EHB715G10004</p>	<p>61.550 €</p>
	<p><b>Remote Control for lift EHB Standard</b> (accessory)</p> <p>Up / Down / Fine / E-stop, 10 m cable,            at master column or startbox</p>	<p>EHB-XACA04</p>	<p>309 €</p>

## Mobile Column Lift EHB Standard for airport ground vehicles (GSE)

	Description	Article-No.	Price
	<p><b>Startbox for EHB707 Standard</b> (accessory)</p> <p>Version: Master control panel with power supply unit Use: For common operation of maximum 6 slave columns EHB707, detachable, to hook at column</p> <p>Operation mode: All / single Connection: 400V / 3Ph / 50Hz / 16A, 10 m power supply cable</p>	EHB7060STBOX	1.172 €
	<p><b>Support Stand LS08</b> (basic version)</p> <p>Capacity: 8.2 t Height: 535 - 790 mm Design: Triangle tubes - light and solid Height adjustment: Plug pin, every 65 mm Colour: Grey RAL7015 Weight: 20 kg</p>	LS08	248 €
	<p><b>Support Stand MS08-LRSV</b> (basic version + spindle)</p> <p>Capacity: 8.2 t Height: 880 - 1410 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 70 mm - Spindle (SV) for fine adjustment</p> <p>Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 34 kg</p>	MS08LRSV	420 €
	<p><b>Support Stand HS08-LRFVSV</b> (basic version + spring + spindle)</p> <p>Capacity: 8.2 t Height: 1350 - 2130 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 50 mm - Spring assistance (FV) - Spindle (SV) for fine adjustment</p> <p>Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 47 kg</p>	HS08LRFVSV	542 €
	<p><b>Support Stand GB15-FV-SV-LR</b> (version with spring, spindle, guide wheels)</p> <p>Capacity: 15 t Height: 1380 - 2010 mm Height adjustment: - Plug pin every 30 mm - Spring assistance (FV) - Spindle (SV) for fine adjustment</p> <p>Wheels: 3 guide wheels (LR), spring-loaded Colour: Grey RAL7015 Weight: 110 kg</p>	GB1502010FVSVLR	1.173 €

