














## Mobile Column Lift GAB for fork lifts

	Description	Article-No.	Price
	<p><b>Mobile Column Lift GAB705-2 Standard</b> (for fork lift vehicles)</p> <p>Capacity: 2 x 5 t = 10 t            Columns: 1 master, 1 slave            Load support: Adjustable fork tines LTR755 to lift at chassis and at lift pillar</p> <p>Fork length: 755 mm            Lifting stroke: 1700 mm            Speed: Approx. 0.8 m/min.            Drive: Electro-hydraulic            Connection: 400 V / 3 Ph / 50 Hz / 16 A            Control: With hydraulic seat valves            Load securing: Hydraulic and mechanical locks            Operation: From each column, Up / Down, All / Single            Cable connection: 1 power supply cable 10 m, interconnect cable 10 m per column, plug at 1 end, closed circuit</p> <p>Travelling device: Hydraulic jack for front and rear wheels, at each column            Protection class: IP 65            Colour: Orange RAL2004</p>	<p>GAB705000002</p>	<p>17.500 €</p>
	<p><b>Remote Control for lift EHB Standard</b> (accessory)</p> <p>Up / Down / Fine / E-stop, 10 m cable, at master column or startbox</p>	<p>EHB-XACA04</p>	<p>309 €</p>
	<p><b>Ramps for Fork Tines LTR755</b> (accessory for column GAB705)</p> <p>Capacity: 5 t (per pair)            Use: To lift fork lift at it's front wheels keeping free access to lifting pillar, also for vehicles with low ground clearance, fork lift to drive onto ramps, ramps to mount on standar fork tines LTR755 of column GAB705</p> <p>Ramp dimensions: Length 670 mm, width 260 mm            Drive-on height: 80 mm            Delivery: 2 ramps</p>	<p>GA7050340000</p>	<p>608 €</p>
	<p><b>Flat Support Tines 400/30</b> (accessory for column GAB705)</p> <p>Capacity: 3 t (per pair)            Length of tines: 400 mm            Height of tines: 30 mm            Use: For vehicles with low ground clearance, to mount at column GAB705</p> <p>Delivery: 2 support tines</p>	<p>PR1810330002</p>	<p>873 €</p>


## Mobile Column Lift GAB for fork lifts

	Description	Article-No.	Price
	<p><b>Support Plate PR183</b> (accessory for column GAB705)</p> <p>Capacity: 4 t Load support: Plate 500 x 475 x 35 mm Use: To lift at round counter weight, to mount at column GAB705</p>	PR183-03	564 €
	<p><b>Stationary 4-Post-Lift GAS10</b> (for fork lift vehicles)</p> <p>Capacity: 10 t Design: 4 stationary columns, 2 platforms, 1 center platform for 3 wheelers, 1 ascending floor ramp</p> <p>Lifting stroke: 1700 mm Platform length: 3800 mm Platform width: 500 mm Platform height: 190 mm Lifting time: Approx. 100 sec. Drive: Electro-hydraulic Connection: 400 V / 3 Ph / 50 Hz / 16 A Load securing: Hydraulic and mechanical locks Protection class: IP 65 Colour: Columns RAL2004 orange           Platforms RAL7015 grey Delivery: Including hydraulic oil and dowel pins</p>	GAS702100000	27.500 €
	<p><b>Support Stand LS08</b> (basic version)</p> <p>Capacity: 8.2 t Height: 535 - 790 mm Design: Triangle tubes - light and solid Height adjustment: Plug pin, every 50 mm Colour: Grey RAL7015 Weight: 20 kg</p>	LS08	248 €
	<p><b>Support Stand LS08-SV</b> (basic version + spindle)</p> <p>Capacity: 8.2 t Height: 625 - 930 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 50 mm                           - Spindle (SV) for fine adjustment Colour: Grey RAL7015 Weight: 24 kg</p>	LS08SV	325 €

## Mobile Column Lift GAB for fork lifts

	Description	Article-No.	Price
	<p><b>Support Stand MS08-LR</b> (basic version)</p> <p>Capacity: 8.2 t                      Height: 790 - 1270 mm                      Design: Triangle tubes - light and solid                      Height adjustment: Plug pin, every 70 mm                      Wheels: 3 guide wheels, spring-loaded                      Colour: Grey RAL7015                      Weight: 30 kg</p>	MS08LR	343 €
	<p><b>Support Stand MS08-LRSV</b> (basic version + spring)</p> <p>Capacity: 8.2 t                      Height: 880 - 1410 mm                      Design: Triangle tubes - light and solid                      Height adjustment: - Plug pin, every 70 mm                      - Spindle (SV) for fine adjustment                      Wheels: 3 guide wheels, spring-loaded                      Colour: Grey RAL7015                      Weight: 34 kg</p>	MS08LRSV	420 €
	<p><b>Support Stand HS0-LR</b> (basic version)</p> <p>Capacity: 8.2 t                      Height: 1260 - 1990 mm                      Design: Triangle tubes - light and solid                      Height adjustment: Plug pin, every 65 mm                      Wheels: 3 guide wheels, spring-loaded                      Colour: Grey RAL7015                      Weight: 40 kg</p>	HS08LR	409 €
	<p><b>Support Stand HS08-LRFV</b> (basic version + spring)</p> <p>Capacity: 8.2 t                      Height: 1260 - 1990 mm                      Design: Triangle tubes - light and solid                      Height adjustment: - Plug pin, every 65 mm                      - Spring assistance (FV)                      Wheels: 3 guide wheels, spring-loaded                      Colour: Grey RAL7015                      Weight: 43 kg</p>	HS08LRFV	465 €
	<p><b>Support Stand HS08-LRSV</b> (basic version + spindle)</p> <p>Capacity: 8.2 t                      Height: 1350 - 2130 mm                      Design: Triangle tubes - light and solid                      Height adjustment: - Plug pin, every 65 mm                      - Spindle (SV) for fine adjustment                      Wheels: 3 guide wheels, spring-loaded                      Colour: Grey RAL7015                      Weight: 44 kg</p>	HS08LRSV	486 €

## Mobile Column Lift GAB for fork lifts

	Description	Article-No.	Price
	<b>Support Stand HS08-LRFVSV</b> (basic version + spring + spindle) Capacity: 8.2 t Height: 1350 - 2130 mm Design: Triangle tubes - light and solid Height adjustment: - Plug pin, every 65 mm - Spring assistance (FV) - Spindle (SV) for fine adjustment Wheels: 3 guide wheels, spring-loaded Colour: Grey RAL7015 Weight: 47 kg	HS08LRFVSV	542 €