












## Stationary Semi-Scissor Platform Lift HDS for heavy duty vehicles

	Description	Article-No.	Price
	<p><b>Semi-Scissor Lift HDS25-8000 (single)</b> (for heavy duty vehicles)</p> <p>Capacity: 25 t (33 t central loaded) Design: 2 platforms with integrated semi-scissors, 1 operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 7950 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A, air 8-10 bar Load securing: Hydraulic and mechanical locks Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS258000F01	49.820 €
	<p><b>Semi-Scissor Lift HDS25-9000 (single)</b> (for heavy duty vehicles)</p> <p>Capacity: 25 t (33 t central loaded) Design: 2 platforms with integrated semi-scissors, 1 operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 8950 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A, air 8-10 bar Load securing: Hydraulic and mechanical locks Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS259000F01	51.280 €
	<p><b>Semi-Scissor Lift HDS25-10000 (single)</b> (for heavy duty vehicles)</p> <p>Capacity: 25 t (33 t central loaded) Design: 2 platforms with integrated semi-scissors, 1 operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 9950 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A, air 8-10 bar Load securing: Hydraulic and mechanical locks Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS2510000F01	53.980 €







## Stationary Semi-Scissor Platform Lift HDS for heavy duty vehicles

	Description	Article-No.	Price
	<p><b>Semi-Scissor Lift HDS25-13000 (single)</b> (for heavy duty vehicles)</p> <p>Capacity: 25 t maximum (depending on load distribution) Design: 2 platforms with integrated semi-scissors, 1 operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 12950 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A, air 8-10 bar Load securing: Hydraulic and mechanical locks Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS2513000F01	64.780 €
	<p><b>Semi-Scissor Lift HDS25-14500 (single)</b> (for heavy duty vehicles)</p> <p>Capacity: 25 t maximum (depending on load distribution) Design: 2 platforms with integrated semi-scissors, 1 operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 14450 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 35A, air 8-10 bar Load securing: Hydraulic and mechanical locks Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS2514500F01	66.850 €
	<p><b>Semi-Scissor Lift HDS50-16000 (tandem)</b> (for heavy duty vehicles)</p> <p>Capacity: 50 t (66 t central loaded) Design: 4 platforms with integrated semi-scissors, 1 central operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 2 x 7950 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 63A, air 8-10 bar Load securing: Hydraulic and mechanical locks Operation: Levante 1 y 2 en modo común o individual Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS5016000F01	101.620 €



## Stationary Semi-Scissor Platform Lift HDS for heavy duty vehicles

	Description	Article-No.	Price
	<p><b>Semi-Scissor Lift HDS50-18000 (tandem)</b> (for heavy duty vehicles)</p> <p>Capacity: 50 t (66 t central loaded) Design: 4 platforms with integrated semi-scissors, 1 central operator's panel</p> <p>Lifting height: 1925 mm floor version, 1570 mm recessed version Platform length: 2 x 8950 mm Platform width: 820 mm Platform height: 355 mm Lifting time: approx. 100 sec. Drive: Electro-hydraulic Connection: 400V / 3Ph / 50Hz / 63A, air 8-10 bar Load securing: Hydraulic and mechanical locks Operation: Lift 1 and 2 in common or individual mode Protection class: IP 65 Colour: Grey RAL7015 Delivery: Incl. hydraulic oil and dowel kit</p>	HDS5018000F01	104.530 €
	<p><b>Ascending Ramps RA235</b> (for floor version only)</p> <p>1 pair, length 2350 mm, incl. dowel kit</p>	HDSF0613-250	1.744 €
	<p><b>Ascending Ramps RA330</b> (for floor version only)</p> <p>1 pair, length 3300 mm, suitable for low-floor vehicles, incl. dowel kit</p>	HDSF0613-330	2.239 €
	<p><b>Inter Platform 45 for HDS50-Tandem</b> (only for floor version)</p> <p>1 pair, 450 mm long, between lift 1 and lift 2, incl. dowel kit</p>	HDS50ZK045	540 €
	<p><b>Remote Control for HDS25</b> (accessory)</p> <p>Handset, Up/Down/E-stop, 10 m cable, at control panel</p>	HDSFB10	152 €

## Stationary Semi-Scissor Platform Lift HDS for heavy duty vehicles

	Description	Article-No.	Price
	<p><b>Pneumatic Sockets for HDS25</b> (accessory) 2 x 2 pneumatic quick-connects, nominal Ø 7.2mm, 8-10 bar, on one platform</p>	HDSDL01	253 €
	<p><b>Electric Sockets 230V for HDS25</b> (accessory) 2 sockets 230V/1Ph/50Hz, max. 750W, IP65, German model, on one platform</p>	HDSST01	264 €
	<p><b>Lighting Kit for HDS25-8000/9000 Single</b> (accessory) 6 fluorescent lamps, IP65, shock-oil resisting, integrated inside of platforms</p>	HDSBL06	1.035 €
	<p><b>Lighting Kit for HDS25-10000/12000 Single</b> (accessory) 8 fluorescent lamps, IP65, shock-oil resisting, integrated inside of platforms</p>	HDSBL08	1.370 €
	<p><b>Lighting Kit for HDS25-1300/14500 Single</b> (accessory) 10 fluorescent lamps, IP65, shock-oil resisting, integrated inside of platforms</p>	HDSBL10	1.849 €
	<p><b>Jacking Beam FL160-200 for HDS25</b> (accessory) Capacity: 16 t Load support: Plate Stroke: 222 mm Drive: 2 cylinders, hydro-pneumatic, 8-10 bar Design: Suitable for distance 1010 mm between platforms Protection: Not to use outdoors or within wash hall Attention: For rolling jack the accessory "Pneumatic Disconnects" is required! For HDS as recessed version the accessory "Position Control" is required!</p>	HDSMHFL160-200	4.161 €

## Stationary Semi-Scissor Platform Lift HDS for heavy duty vehicles

Description	Article-No.	Price	
<p><b>Position Control for Jacking Beam MH14</b> (accessory, for recessed version only) Supervision of parking position of jack MH14 when lowering into pit, only required for recessed version of HDS lift</p>	HDSMH-UF	130 €	
	<p><b>Bio Oil for HDS25</b> (accessory, instead of standard oil) Synthetic oil, biodegradable, -10 to +70°C</p>	HDS25SYN	544 €
<p><b>Galvanizing of HDS25-8000</b>  High resistant hot galvanizing (120my) plus additional priming (140my) and final coating (60my), colour Grey RAL9006.</p>	HDSFV-8000	9.943 €	
<p><b>Galvanizing of HDS25-9000</b>  High resistant hot galvanizing (120my) plus additional priming (140my) and final coating (60my), colour Grey RAL9006.</p>	HDSFV-9000	10.264 €	
	<p><b>Wheel Carriage RW5.16</b>  Capacity: 500 kg Lifting stroke: 1600 mm Load support: Adjustable fork for wheels Ø 500 - 1800 mm, length 650 mm, divided rollers for twin wheels Drive: Manual winch Travelling device: 2 fixed rollers, 2 guide wheels Colour: Grey RAL7015</p>	RW1300000	1.847 €